

TELEPHONE DUCT



Type B (Concrete Encased)

Type C (Direct Bury or
Concrete Encased)

Type D (Exposed)

Sweeps ("C" Duct)

Telephone Duct – Type B, C, & D

Telephone Duct Type B

Prime Conduit® Telephone Duct Type B is designed for use in concrete encased installations. Type B duct harmonized with Bellcore/Telcordia CA08546.

Nom. Size	Part Number 20'	Std. Crate Qty. 20' (ft.)	Approx. Wt. per 100 ft (lbs.)	Avg. O.D. (in.)	*Min. Wall (in.)	Min. Bell Length (in.)
4"	68315-020 (Gray)	1,260	100	4.350	0.090	3
Heavy Wall:						
4"	68415W-020 (White)	1,260	110	4.350	0.100	3

*Estimated minimum wall thickness to meet performance criteria (500,000 modulus compound)
Length is 20' 3" (includes length of bell)
For concrete encasement only

Telephone Duct Type C

Prime Conduit® Telephone Duct Type C is designed for direct burial or concrete encased applications. Type C duct is analogous with Bellcore/Telcordia CA08546 and NEMA TC-10.

Nom. Size	Part Number 20'	Std. Crate Qty. 20' (ft.)	Approx. Wt. per 100 ft (lbs.)	Avg. O.D. (in.)	*Nom. Avg. Wall (in.)	Min. Bell Length (in.)
4"	68515-020 (Gray)	1,260	150	4.350	0.145	3
4"	68515W-020 (White)	1,260	150	4.350	0.145	3
4"	68515WLB-020 (White)	1,260	150	4.350	0.145	6

*Estimated wall thickness to meet performance criteria
Length is 20' 3" (includes length of bell)
For direct bury or concrete encasement only

Telephone Duct Type D

Prime Conduit® Telephone Duct Type D is designed to be used in exposed applications.
White only.


Nom. Size	Part Number 20'	Std. Crate Qty. 20' (ft.)	Approx. Wt. per 100 ft (lbs.)	Avg. O.D. (in.)	*Min. Wall (in.)	Min. Bell Length (in.)
4"	68615-020 (White)	1,260	151	4.350	0.160	3

*Estimated minimum wall thickness to meet performance criteria
Length is 20' 3" (includes length of bell)
For exposed applications only


Telephone Duct Sweeps

Manufactured from Heavy Wall "C" Duct

90° Sweeps - Belled



45° Sweeps - Belled



Part Number	Radius	Crate Qty
Gray:		
TP9CN	1'6"	30
TP9DN	2'	30
TP9FN	3'	30
TP9HN	4'	30
TP9IN	5'	30
TP9JN	6'	30
TP9MN	9'	20
TP9NN	10'	20
TP9SN	12'6"	6
TP9TN	15'	10
TP9UN	20'	10
White:		
TW9DN	2'	30
TW9FN	3'	30
TW9HN	4'	30
TW9IN	5'	30
TW9JN	6'	30
TW9MN	9'	20
TW9NN	10'	20
TW9SN	12'6"	20
TW9TN	15'	20

Part Number	Radius	Crate Qty
Gray:		
TP7DN	2'	30
TP7FN	3'	30
TP7HN	4'	30
TP7ON	4'6"	30
TP7IN	5'	30
TP7JN	6'	30
TP7MN	9'	30
TP7NN	10'	30
TP7RN	12'	30
TP7SN	12'6"	12
TP7TN	15'	12
TP7UN	20'	12
White:		
TW7DN	2'	30
TW7FN	3'	30
TW7HN	4'	30
TW7ON	4'6"	30
TW7IN	5'	30
TW7JN	6'	30
TW7MN	9'	30
TW7NN	10'	30
TW7RN	12'	30
TW7SN	12'6"	30
TW7TN	15'	30

Note: Sweeps 72" and larger may be shipped in segments. Consult factory for specifics.


Diameter: 4"

Straight End Length: 3"

Telephone Duct Sweeps


Manufactured from Heavy Wall "C" Duct

30° Sweeps - Belled




Part Number	Radius	Crate Qty
Gray:		
TP6FN	3'	30
TP6HN	4'	30
TP6JN	6'	30
TP6NN	10'	30
TP6RN	12'	25
TP6SN	12'6"	25
TP6TN	15'	30
White:		
TW6FN	3'	30
TW6HN	4'	30
TW6JN	6'	30
TW6MN	9'	48/BOX
TW6NN	10'	30
TW6RN	12'	30
TW6SN	12'6"	30
TW6TN	15'	30

22 1/2° Sweeps - Belled



Part Number	Radius	Crate Qty
Gray:		
TP5DN	2'	60
TP5FN	3'	5/BOX
TP5HN	4'	5
TP5IN	5'	25
TP5JN	6'	30
TP5MN	9'	30
TP5RN	12'	25
TP5SN	12'6"	30
TP5TN	15'	30
TP5UN	20'	30
TP5VN	25'	30
White:		
TW5DN	2'	10/BOX
TW5FN	3'	5/BOX
TW5HN	4'	30
TW5JN	6'	30
TW5MN	9'	30
TW5SN	12'6"	36

11 1/4° Sweeps - Belled



Part Number	Radius	Crate Qty
Gray:		
TP3DN	2'	60
TP3FN	3'	10/BOX
TP3HN	4'	50
TP3IN	5'	50
TP3JN	6'	5
TP3SN	12'6"	30
White:		
TW3DN	2'	10/BOX
TW3FN	3'	10/BOX
TW3HN	4'	5

Note: Sweeps 72" and larger may be shipped in segments. Consult factory for specifics.

Diameter: 4"

Straight End Length: 3"